

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An assembly for effecting the condition of a mitral valve annulus of a heart comprising:

a guide wire configured to be advanced to the coronary sinus of the heart; and

a resilient mitral valve annulus device configured to be deformed and received on the guide wire and advanced into the coronary sinus of the heart on the guide wire and that reshapes the mitral valve annulus when in the coronary sinus of the heart[[]]; and

a forming element coupled to the mitral valve annulus device, the forming element extending proximally to a location outside the body for adjusting the curvature of the mitral valve annulus device;

wherein the mitral valve annulus device is ~~further configured to change~~ adjustable from a first shape toward a second shape having a curvature adapted to reshape the mitral valve annulus when in the coronary sinus of the heart, and wherein ~~the coronary sinus has a natural curvature, the curvature of~~ changing the mitral valve annulus device from the first shape to the second shape being different than the natural affects the radius of curvature of the coronary sinus such that the mitral valve annulus device presses a portion of the coronary sinus against the mitral valve annulus to reshape the mitral valve annulus.

2-7 (Cancelled)

8. (Original) The assembly of claim 1 wherein the guide wire is formed of a material visible under X ray.

9-10 (Cancelled)

11. (Previously Presented) The assembly of claim 1 further including an elongated introducer configured to be received on the guide wire.

12. (Cancelled)

13. (Original) The assembly of claim 11 wherein the assembly further includes a releasable locking mechanism configured to releasably lock the device to the introducer.

14. (Previously Presented) The assembly of claim 11 further including a guide tube having an inner lumen dimensioned for receiving the device and introducer when the device and introducer are received on the guide wire.

15-25. (Cancelled)

26. (Currently Amended) An assembly for effecting the condition of a mitral valve annulus of a heart comprising:

a guide wire configured to be advanced to the coronary sinus of the heart;

a resilient mitral valve annulus device configured to be received on the guide wire and advanced into the coronary sinus, the mitral valve annulus device being ~~configured~~ transferable to a different radius of curvature for selectively altering a curvature of the coronary sinus to press a portion of the coronary sinus against the mitral valve annulus with sufficient force to reshape the mitral valve annulus and reduce a gap of a mitral valve in the mitral valve annulus when in the coronary sinus of the heart; and

at least one forming element coupled to the mitral valve annulus device for ~~selectively manipulating a shape~~ the radius of curvature of the mitral valve annulus device from a location outside the venous system.

27. (Currently Amended) The assembly of claim 26, wherein the forming element is configured to ~~alter a~~ reduce a radius of curvature of the mitral valve annulus device.

28. (Canceled)